

livecookintable® CHEFPOWER

Mobile and modular battery system for operating livecookintable® front cooking and buffet stations, consisting of the CHEFPOWER_core base station and the CHEFPOWER_stack supplementary battery.



TECHNICAL DATA:

CHEFPOWER_core:

- semi-solid-state battery with a capacity of 6.4 kWh, 3680 W
- dimensions: 73 x 35 x 44 cm
- weight: 59 kg
- outputs: 4 x Schuko 16A, Auto 10A, 2 USB-C 20V/100W, 2 USB-C 12V/20W, 1 USB-A, Andersen 12,6 V/30A, Zen T2
- output voltage either 230V 50Hz or 120V 60Hz
- charging at the Schuko plug in 2 hours of operation with either 230V 50Hz or 120V 60Hz
- uninterruptible Power Supply (UPS)
- motorized wheels
- MC4 to XT-90 Adapter
- overload protection
- own app via integrated 2.4 GHz WLAN

CHEFPOWER_stack:

- supplementary battery
- dimensions: 69 x 28,5 x 27,4 cm
- weight: 64 kg
- same performance data as base station CHEFPOWER_core
- Either stacked on base station or connected via connecting cable
- must be operated via a CHEFPOWER_core base station

 **livecookintable®**

Design made in Germany